



## CANOPY RECESSED LED

Introducing the **CANOPY RECESSED**. This luminaire is a rectangular recessed highbay with high power LEDs and efficient optics, providing multiple light distribution options



# CANOPY RECESSED




## APPLICATIONS


- Fuel Stations
- Freezer Rooms
- Industrial Developments
- Commercial Developments
- Warehousing

## PRODUCT SPECIFICATIONS

|                         |                           |
|-------------------------|---------------------------|
| LED Driver              | Internal                  |
| Input Voltage           | 220-240 V                 |
| Dimming Options         | On request                |
| Flicker Rating          | < 5%                      |
| Low Ripple Current      | Yes                       |
| Light Source            | LED                       |
| Power Factor            | > 0.9                     |
| Available CCT           | 4000K, 5700K              |
| CRI                     | > 80                      |
| Lifetime                | L80B10 ≥ 50 000 hours     |
| Application Temperature | -20°C to 40°C             |
| Available Emergency     | On request                |
| Warranty                | 5 Years - T's & C's apply |
| IP Rating               | IP66                      |
| Housing Material        | Aluminium                 |
| Finish                  | White                     |
| Diffuser                | Clear Lensed              |
| Mounting                | Recessed                  |



68mm



| Luminaire Wattage | Output (Lumens) | Colour Temperature | Efficacy (lm/W) | CRI Rating | Dimensions L x W x H | Beam Angle | Reference Code |
|-------------------|-----------------|--------------------|-----------------|------------|----------------------|------------|----------------|
| 140               | 16103           | 4000K              | 115             | >80        | 540mm x 540mm x 68mm | 90°        | LAICR-140-4K   |
| 140               | 16627           | 5700K              | 119             | >80        | 540mm x 540mm x 68mm | 90°        | LAICR-140-57K  |

# LIGHTALLIANCE

Projects (PTY) Ltd.

Partners in *Lighting Solutions*

### Disclaimer:

Component manufacturer data is used and could vary +-10%

We reserve the right to amend or change data without prior notification.

E&OE