

DOWNLIGHTS



LARA

LED

The stylish **LARA** recessed downlight has a sleek design with a recessed LED light source reducing glare. It's UGR <19 rating makes the **LARA** suitable for retail and office lighting.

LIGHT ALLIANCE

Projects (PTY) Ltd.

Partners in *Lighting Solutions*



LARA




APPLICATIONS

- Public Buildings
- Industrial Developments
- Ablutions
- Commercial Developments
- Retail Developments
- Shopping Malls



PRODUCT SPECIFICATIONS

LED Driver	External
Input Voltage	220-240 V
Dimming Options	DALI, Other
Flicker Rating	< 5%
Low Ripple Current	Yes
Light Source	LED (COB)
Power Factor	> 0.95
Available CCT	4000K, 3000K
CRI	> 90
Lifetime	Up to 80 000 hours
Application Temperature	Ta < 35°C
Available Emergency	1Hr - 3Hr
Warranty	5 Years - T's & C's apply
IP Rating	44
Housing Material	Aluminium
Finish	White
Diffuser	Specular Reflector
Mounting	Recessed



Luminaire Wattage	Output (Lumens)	Colour Temperature	Efficacy (lm/W)	CRI Rating	Dimensions (A x B)	Cutout Size	Beam Angle	Reference Code
10	1080	4000K	108	>90	110mm x 75mm	90mm	60°	DL361-3-010-4K
10	1080	3000K	108	>90	110mm x 75mm	90mm	60°	DL361-3-010-3K
18	1944	4000K	108	>90	150mm x 97mm	120mm	60°	DL361-4-018-4K
18	1944	3000K	108	>90	150mm x 97mm	120mm	60°	DL361-4-018-3K
35	3780	4000K	108	>90	240mm x 142mm	210mm	60°	DL361-8-035-4K
35	3780	3000K	108	>90	240mm x 142mm	210mm	60°	DL361-8-035-3K

LIGHT ALLIANCE

Projects (PTY) Ltd.
Partners in Lighting Solutions

Disclaimer:

Component manufacturer data is used and could vary +-10%
We reserve the right to amend or change data without prior notification.
E&OE