



ZOLA

LED

The **ZOLA** is a Coastal grade LED flood with non corrosive body and 304 grade Stainless Steel bracket.

LIGHTALLIANCE

Projects (PTY) Ltd.

*Partners in **Lighting Solutions***



ZOLA



APPLICATIONS


- Public Buildings
- Industrial Developments
- Parking lots
- Commercial Developments

PRODUCT SPECIFICATIONS


LED Driver	Internal
Input Voltage	220-240 V
Dimming Options	None
Flicker Rating	< 5%
Low Ripple Current	Yes
Light Source	LED
Power Factor	> 0.9
Available CCT	6000K
CRI	> 80
Lifetime	Up to 50 000 hours
Application Temperature	-30°C to 40°C
Available Emergency	1Hr - 3Hr (remote)
Warranty	5 Years - T's & C's apply
IP Rating	65
Housing Material	Die Cast Aluminium
Finish	Black
Diffuser	PMMA Opal Diffuser - UV Stable
Mounting	Surface Mount




30W




50W



100W



150W



Luminaire Wattage	Output (Lumens)	Colour Temperature	Efficacy (lm/W)	CRI Rating	Dimensions	Beam Angle	Reference Code
30	3900	6000K	130	>80	Refer to sketch above	120°	LAFLC-030-6K
50	6500	6000K	130	>80	Refer to sketch above	120°	LAFLC-050-6K
100	13000	6000K	130	>80	Refer to sketch above	120°	LAFLC-100-6K
150	19500	6000K	130	>80	Refer to sketch above	120°	LAFLC-150-6K

LIGHTALLIANCE

Projects (PTY) Ltd.
Partners in Lighting Solutions

Disclaimer:

Component manufacturer data is used and could vary +-10%
We reserve the right to amend or change data without prior notification.
E&OE